

SPECIFICATION FOR YOLDAL CHIP LED

PART. NO: UBSM0603WW

YOLDAL

■ Features:

- Compatible with automatic placement equipment.
- Compatible with infrared and vapor phase reflow solder process.
- Mono-color type.

■ Descriptions:

- Much smaller than lead frame type components, enable smaller board size, higher packing density, reduced storage space and finally smaller equipment to be obtained.
- Lightweight for miniature applications.

■ Applications:

- **Model Railroad and Auto Headlights**
- Backlighting
- Indicators
- Switch and symbol
- General use





■ Benefits:

- Low Energy Consumptions
- Low Maintenance Costs
- High Application Design Flexibility
- High Reliability
- Very Competitive prices


■ Device material descriptions:

Part ID	Chip		Lens Color
UBSM0603WW	Material	Emitted Color	Yellow
	GaN	Sunny White	Diffused

■ Package Outline Dimensions:



For reflow soldering (proposed)



Notes: Tolerances Unless Dimensions,
0.1mm, Angles $\pm 0.5^\circ$, Unit: mm

■ **Absolute maximum ratings:**


Parameter	Symbol	Rating	Unit
Reverse Voltage	V_R	5	V
Forward Current	I_F	20	mA
Operating temperature	T_{opr}	-25 ~ +80	°C
Storage Temperature	T_{stg}	-30 ~ +85	°C
Soldering temperature	T_{sol}	260 (for 5 Second)	°C
Power Dissipation	P_d	80	mW
Electrostatic Discharge*	ESD	150	V
Peak Forward Current (Duty 1/10 @1KHz)	I_{PF}	100	mA

*Static Electricity Sensitive, care must be fully taken when handling this product.

■ **Electro-Optical characteristics:**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	I_V	-----	200	-----	mcd	$I_F=20$ mA
Viewing angle	2θ 1/2	-----	120	-----	Deg.	$I_F=20$ mA
Forward Voltage	V_F	-----	3.2	3.5	V	$I_F=20$ mA
Reverse Current	I_R	-----	-----	50	uA	$V_R=5$ V
Chromaticity*	X	-----	0.440	-----	-----	$I_F=20$ mA
Coordinate	Y	-----	0.450	-----	-----	

*C.I.E. 1931 Chromaticity Diagram.



■ Precautions For Use

1. Over Current Proof

Resistors must properly applied for protection, slightly voltage shift will cause big current change, BURN OUT will happen.

2. Storage Time


2.1. The operating temperature and RH: 5 °C ~ 35 °C, RH60%.

2.2. Once the package is opened, the products should be used within a week. Otherwise, they should be kept in a damp proof box with desiccating agent. Taping life considering, strongly suggest using this products within one year from date of production.

2.3. Package opened more than one week in an normal atmosphere environment, before soldering, they should be treated at 60 °C ± 5 °C for 15 hrs.


2.4. When the desiccant agent changed to pink, the device should be treated as condition 2.3.

■ Soldering Heat Reliability




■ Rework

1. Rework must be finished within 5 sec. under 245 °C.
2. The head of Iron must not touch the copper foil.
3. Twin-head type is preferred.



■ Reflow Temp. / Time



■ Soldering Iron

Basic spec is ≤5 sec. / 260 °C. If temperature is higher, time should be shorted (+10 °C→-1 sec.). Power dissipation of Iron should be smaller than 15 W, and temperature should be controllable. Surface temperature of the device should be under than 230 °C.